



Low-E ThermaSheet®

An ICC Approved Stand Alone Insulated Roofing Underlayment

- * Self Seals Around Fasteners
- * Great For New Or Re-Roofing
- * TDI, CA & FL Approved
- * For Use Under Shingles, Metal Roof, Clay Tile & More
- * Lowers Attic Temperature
- * Increases Energy Savings
- * Excellent Vapor Barrier
- * Built In Overlap Means Full Five Square Coverage

LOW-E THERMASHEET®

FEATURES AND SPECIFICATIONS

PRODUCT DESCRIPTION:

ThermaSheet® Insulation may be installed directly under shingles and ICC, CBC, CRC and FRC evaluation (ESR-3652) allows it to be used as a stand alone alternative to felt paper and other traditional underlayments. Simply install ThermaSheet® as you would any other underlayment using the overlapping flange as a rain drip edge. Shingles, etc. are then installed as per the manufacturers instructions.

PRODUCT NAME: ThermaSheet®

PRODUCT CODES: 4LMPX - 1/8", 4LFPX - 7/32"

WIDTH: 4' **LENGTH:** 125' (with 4" overlapping flange)

WEIGHT: 21 Lbs.

R-VALUE: Under Shingles - 4LMPX 0.5, 4LFPX 1.03

R-VALUE: R-9 downward heat flow only (With 1.5" airspace)

CORE MATERIAL: Polyethylene

FACING: 99.4% Polished Aluminum

PERM RATING: ASTM E-96 0.0008

EMITTANCE: ASTM C-1371 0.03



UNDER METAL



STONE COATED
STEEL



CLAY TILE

Thermal imaging of an attic without
ThermaSheet® roofing underlayment.
Temperature is 129°



Thermal imaging of the same attic WITH
ThermaSheet® roofing underlayment.
Temperature is 98°



For more information please visit our website at www.low-e.com
or call 1-800-BUY-LOWE (800-289-5693)